

SAFETY DATA SHEET

1. SUBSTANCE AND SOURCE IDENTIFICATION

Product Identifier

SRM Number: 2298
SRM Name: Sulfur in Gasoline (High Octane)
Other Means of Identification: Not applicable.

Recommended Use of This Material and Restrictions of Use

This Standard Reference Material (SRM) is a high octane unleaded motor gasoline (primarily an alkylate blend) intended for use in the evaluation of methods and the calibration of instruments used in the determination of total sulfur in gasoline or materials of similar matrix. A unit of SRM 2298 consists of 5 amber ampoules, each containing approximately 20 mL of gasoline.

Company Information

National Institute of Standards and Technology
 Standard Reference Materials Program
 100 Bureau Drive, Stop 2300
 Gaithersburg, Maryland 20899-2300

Telephone: 301-975-2200
 FAX: 301-948-3730
 E-mail: SRMMSDS@nist.gov
 Website: <http://www.nist.gov/srm>

Emergency Telephone ChemTrec:
 1-800-424-9300 (North America)
 +1-703-527-3887 (International)

2. HAZARDS IDENTIFICATION

Classification

| | | |
|-------------------------|-------------------------|-------------|
| Physical Hazard: | Flammable liquid | Category 2 |
| Health Hazard: | Skin Irritation | Category 2 |
| | Eye Irritation | Category 2B |
| | Germ Cell Mutagenicity | Category 1B |
| | Carcinogenicity | Category 1B |
| | Reproductive Toxicity | Category 2 |
| | STOT, Single Exposure | Category 3 |
| | STOT, Repeated Exposure | Category 1 |
| | Aspiration Hazard | Category 1 |

Label Elements

Symbol



Signal Word

Danger

Hazard Statement(s)

| | |
|-----------|---|
| H225 | Highly flammable liquid and vapor. |
| H304 | May be fatal if swallowed and enters airways |
| H315+H320 | Causes skin and eye irritation. |
| H340 | May cause genetic effects. |
| H350 | May cause cancer. |
| H361 | Suspected of damaging fertility or the unborn child. |
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs (liver, kidneys, and nervous system) through prolonged or repeated exposure. |

Precautionary Statement(s)

| | |
|----------------|--|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P210 | Keep away from heat, sparks, open flames, hot surfaces. — No smoking. |
| P233 | Keep container tightly closed. |
| P241 | Use explosion-proof electrical, ventilating, and lighting equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P260 | Do not breathe fumes, mist, vapors, or spray. |
| P264 | Wash hands thoroughly after handling. |
| P270 | Do not eat, drink, or smoke when using this product. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves, eye protection, protective clothing. |
| P301+P310+P331 | If swallowed: Immediately call a doctor. Do NOT induce vomiting. |
| P302+P361+P352 | If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water. |
| P304+P340 | If inhaled: Remove person to fresh air and keep comfortable for breathing. |
| P305+P351+P338 | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical attention. |
| P332+P337+P313 | If skin or eye irritation occurs: get medical attention. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |
| P403+P235+P233 | Store in a well-ventilated place. Keep cool. Keep container tightly closed. |
| P405 | Store locked up. |
| P501 | Dispose of contents and container according to local regulations. |

Hazards Not Otherwise Classified: None.**Ingredients(s) with Unknown Acute Toxicity:** None.**3. COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS****Substance:** Gasoline**Other Designations:** Synthetic gasoline blend.

Note: The concentrations of the compounds that are not listed in this section are below the reportable limit for hazardous components (1 % or greater) and carcinogens (0.1 % or greater), required by OSHA, 29 CFR 1910.1200 (g)(2)(i)(C)(1), for SDS information. For actual concentrations, see the NIST Certificate of Analysis.

| Hazardous Component | CAS Number | EC Number (EINECS) | Nominal Mass Concentration (%) |
|--|------------|--------------------|--------------------------------|
| Gasoline | 8006-61-9 | 232-349-1 | 100 |
| Individual Hazardous Components | | | |
| Benzene | 71-43-2 | 200-753-7 | 1 |
| n-Butane | 106-97-8 | 203-448-7 | 2 |
| Cyclopentane | 287-92-3 | 206-016-6 | 4 |
| 2,3-Dimethylhexane | 584-94-1 | 209-547-1 | 2 |
| 2,4-Dimethylhexane | 589-43-5 | 209-649-6 | 4 |
| 2,5-Dimethylhexane | 592-13-2 | 209-745-8 | 2 |
| 2,3-Dimethylpentane | 565-59-3 | 209-208-0 | 3 |
| 2,4-Dimethylpentane | 108-08-7 | 203-548-0 | 2 |
| n-Hexane | 110-54-3 | 203-777-6 | 1 |
| Isopentane | 78-78-4 | 201-142-8 | 9 |
| 2-Methylpentane | 107-83-5 | 203-523-4 | 2 |
| 3-Methylpentane | 96-14-0 | 202-481-4 | 1 |
| n-Pentane | 109-66-0 | 203-692-4 | 7 |
| 2,2,4-Trimethylpentane | 540-84-1 | 208-759-1 | 25 |
| 2,3,4-Trimethylpentane | 565-75-3 | 209-292-6 | 13 |
| Toluene | 108-88-3 | 203-625-9 | 14 |

4. FIRST AID MEASURES

Description of First Aid Measures

Inhalation: If adverse effects occur, remove to well-ventilated (uncontaminated) area. If breathing is difficult, qualified personnel may administer oxygen. If not breathing, qualified personnel should give artificial respiration. Seek immediate medical attention.

Skin Contact: Rinse affected skin with water for at least 15 minutes, then wash thoroughly with soap or mild detergent and water. If skin irritation persists, seek medical aid and bring the container or label.

Eye Contact: Immediately flush eyes, including under the eyelids, with copious amounts of water for at least 15 minutes. Seek immediate medical attention.

Ingestion: Aspiration hazard. Do not induce vomiting. Contact local poison control immediately; if vomiting occurs, keep head lower than hips to prevent aspiration. If unconscious, turn head to side; get medical attention immediately.

Most Important Symptoms/Effects, Acute and Delayed: Aspiration hazard, blood damage, liver damage, central nervous system depression, cancer hazard (in humans).

Indication of any immediate medical attention and special treatment needed, if necessary: If any of the above symptoms are present, seek immediate medical attention.

5. Fire Fighting Measures

Fire and Explosion Hazards: Severe fire hazard. Vapor/air mixtures are explosive above the flash point. Vapors or gases may ignite at distant ignition sources and flash back. See Section 9, "Physical and Chemical Properties" for flammability properties.

Extinguishing Media

Suitable: Regular dry chemical, carbon dioxide, water, or alcohol-resistant foam.

Unsuitable: None listed.

Specific Hazards Arising from the Chemical: Not applicable.

Special Protective Equipment and Precautions for Fire-Fighters: Move container from fire area if it can be done without personal risk. Avoid inhalation of material or combustion by-products. Wear full protective clothing and NIOSH-approved self-contained breathing apparatus (SCBA).

NFPA Ratings (0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Health = 3

Fire = 3

Reactivity = 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Use suitable protective equipment; see Section 8, "Exposure Controls and Personal Protection". Keep out of waters supplies and sewers.

Methods and Materials for Containment and Clean up: Avoid heat, flames, sparks and other sources of ignition. Stop leak if possible without personal risk, with water spray to reduce vapors. Absorb spilled material with sand or non-combustible material and collect in appropriate container for disposal.

7. HANDLING AND STORAGE

Safe Handling Precautions: See Section 8, "Exposure Controls and Personal Protection".

Storage and Incompatible Materials: Store in a well-ventilated area. Keep separated from incompatible substances (see Section 10, "Stability and Reactivity").

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

| Exposure Limits | | | |
|--|--|--|--|
| Components | OSHA (PEL) | ACGIH (TLV) | NIOSH (REL) |
| Gasoline | There is no PEL for gasoline in general industry in 29 CFR 1910.1000 Z-1 Table. ^(a) | TWA: 300 ppm STEL: 500 ppm | NOEL ^(b) |
| <i>Individual Components of Reformulated Gasoline in SRM 2298 with occupational exposure limits.</i> | | | |
| Benzene | TWA: 1 ppm STEL: 5 ppm ^(c) Ceiling: 25 ppm ^(c) Action level: 0.5 ppm ^(d) | TWA: 0.5 ppm STEL: 2.5 ppm Skin ^(e) | TWA: 0.1 ppm STEL: 1 ppm IDLH: 500 ppm |
| n-Butane | NOEL | TWA: 1000 ppm | TWA: 800 ppm (1900 mg/m ³) |
| Cyclopentane | NOEL | TWA: 600 ppm | TWA: 600 ppm(1720 mg/m ³) |
| 2,3-Dimethylpentane, 2,4-Dimethylpentane | NOEL | TWA: 400 ppm STEL: 500 ppm | NOEL |
| n-Hexane | TWA: 1800 mg/m ³ (500 ppm) | TWA: 50 ppm Skin ^(e) | TWA: 180 mg/m ³ (50 ppm) IDLH: 1100 ppm ^(f) |
| Isopentane | NOEL | TWA: 600 ppm | NOEL |
| n-Pentane | TWA: 1000 ppm (2950 mg/m ³) | TWA: 1000 ppm | TWA: 120 ppm (350 mg/m ³) Ceiling ^(c) : 610 ppm (1800 mg/m ³) IDLH: 1500 ppm ^(f) |
| Toluene | TWA: 200 ppm Ceiling: 300 ppm | TWA: 20 ppm | TWA: 375 mg/m ³ (100 ppm) STEL: 560 mg/m ³ (150 ppm) IDLH: 500 ppm |

^(a) The composition of these materials varies greatly. The content of benzene, other aromatics and additives should be determined individually.

^(b) NOEL: No occupational exposure limits established.

^(c) 15 minutes.

^(d) Cancer hazard, flammable, see 29 CFR 1910.1028.

^(e) Skin – Potential significant contribution to overall exposure by the cutaneous route.

^(f) IDLH based off of 10 % LEL.

Engineering Controls: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Personal Protection Measures: In accordance with OSHA 29 CFR 1910.132, subpart I, wear appropriate Personal Protective Equipment (PPE) to minimize exposure to this material.

Respiratory Protection: If workplace conditions warrant a respirator, a respiratory protection program that meets OSHA 29CFR 1910.134 must be followed. Refer to NIOSH 42 CFR 84 for applicable certified respirators.

Eye Protection: Splash resistant safety goggles and emergency eyewash are recommended.

Skin and Body Protection: Chemical resistant clothing and gloves are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

| Properties | Gasoline |
|--|----------------------------------|
| Molar Mass (g/mol) | not applicable |
| Molecular Formula | not applicable |
| Appearance (physical state, color, etc.) | clear, colorless to amber liquid |
| Odor | distinct odor |
| Odor threshold | 0.25 ppm |
| pH | not available |
| Evaporation rate | not available |

| Properties | Gasoline |
|--|---|
| Melting point/freezing point | not available |
| Specific Gravity (water = 1) | 0.7 to 0.8 at 15 °C |
| Density ^(a) | 694.1 kg/m ³ at 15 °C |
| Vapor Pressure | not available |
| Vapor Density (air = 1) | 3 to 4 |
| Viscosity | not available |
| Solubilities | water: insoluble; soluble in absolute alcohol, ether, chloroform, and benzene |
| Partition coefficient (n-octanol/water) | not available |
| Thermal Stability Properties | |
| Autoignition Temperature | 280 °C to 456 °C (536 °F to 853 °F) |
| Thermal Decomposition | not applicable |
| Initial boiling point and boiling range | 38 °C to 204 °C (100 °F to 399 °F) |
| Explosive Limits, LEL (Volume %) | 1.2 % |
| Explosive Limits, UEL (Volume %) | 7.6 % |
| Flash Point (Estimate) | -35 °C (-31 °F) |
| Flammability (solid, gas) | not applicable |

^(a) Physical property listed in the NIST Certificate of Analysis. Value is not certified.

10. STABILITY AND REACTIVITY

Reactivity: This material is stable at normal temperatures and pressure.

Stability: Stable Unstable

Possible Hazardous Reactions: Not applicable.

Conditions to Avoid: Avoid heat, flames, sparks, and other sources of ignition. Minimize contact with material. Avoid inhalation of material or combustion by-products. Keep out of water supplies and sewers.

Incompatible Materials: Oxidizing materials, halogens, metal salts, acids, bases, combustible materials.

Hazardous Decomposition: Oxides of carbon.

Hazardous Polymerization: Will Occur Will Not Occur

11. TOXICOLOGICAL INFORMATION

Route of Exposure: Inhalation Skin Ingestion

Symptoms Related to the Physical, Chemical and Toxicological Characteristics: Skin irritation, eye irritation, central nervous system depression, and nerve damage.

Potential Health Effects (Acute, Chronic, and Delayed)

Inhalation: Acute exposure may result in irritation, headache, drowsiness, dizziness, vomiting, sleep disturbances, emotional disturbances, tremors, loss of coordination, visual disturbances, chest pain, difficulty breathing, irregular heartbeat, lung congestion, internal bleeding, blood disorders, kidney damage, liver damage, paralysis, brain damage, convulsions, unconsciousness, and coma. Chronic exposure may result in the same effects as acute exposure but with changes in body temperature, changes in blood pressure, loss of appetite, menstrual disorders, nerve damage, reproductive effects, and cancer.

Skin Contact: Acute exposure may cause irritation, skin disorders. Chronic exposure may cause irritation, skin disorders, tingling sensation, and allergic reactions.

Eye Contact: Exposure may result in irritation and other reversible effects.

Ingestion: Aspiration hazard. Exposure may cause the same effects as listed for inhalation. Repeated or prolonged ingestion may result in reproductive effects and cancer.

Numerical Measures of Toxicity

Acute Toxicity: Not classified.

| Components | Acute Toxicity |
|------------------------|--|
| Gasoline | Rat, Inhalation, LC50: 300 g/m ³ (5 min) Rat, Oral, LD50: 13 600 mg/kg |
| Benzene | Rat, Oral, LD50: 930 mg/kg; 1 mL/kg; 6400 mg/kg; 1800 mg/kg Rat, Inhalation, LC50: 10 000 ppm (7 h) |
| <i>n</i> -butane | Rat, Inhalation, LC50: 658 g/m ³ (4 h) |
| Cyclopentane | Rat, Oral LD50: 11 400 mg/kg Rat, Inhalation LC50: 106 g/m ³ (4 h) |
| 2,2,4-Trimethylpentane | Rat, Oral LD50: >2500 mg/kg Rat, Inhalation LC50: 47.4 g/L (1 h) |
| <i>n</i> -Hexane | Rat, Oral, LD50: 15 840 mg/kg Rat, Inhalation, LC50: 48 000 ppm (4 h) Rabbit, Dermal LD50: 3000 mg/kg |
| Isopentane | Rat, Inhalation LC50: 280 g/m ³ (4 h) |
| <i>n</i> -pentane | Rat, Oral LD50: >2000 mg/kg Rat, Inhalation LC50: 364 g/m ³ (4 h) Rabbit, Dermal LD50: 3000 mg/kg |
| Toluene | Rat, Oral, LD50: 636 mg/kg; 2600 mg/kg Rat, Inhalation, LC50: 12.5 mg/L (4 h); 49 g/m ³ (4 h) Rabbit, Dermal LD50: 14 100 µL/kg |

Skin corrosion/irritation: Category 2

Gasoline, Rabbit skin: 500 µL (24 h) – mild

Toluene, Rabbit skin: 435 mg (24 h) – mild; 20 mg (24 h) – moderate; 500 mg – moderate

Benzene, Rabbit skin: 20 mg (24 h) moderate; rabbit open skin: 15 mg (24 h) – mild

Serious eye damage/eye irritation: Category 2B

Gasoline, Human eyes: 140 ppm (8 h) – mild; man eyes: 500 ppm (1 h) – moderate

Toluene, Human eyes: 300 ppm; Rabbit eyes: 870 µg – mild

n-Hexane, Rabbit eyes: 10 mg – mild; Vapors at 880 ppm for 15 min caused irritation.

Benzene, Rabbit eyes: 88 mg – moderate; 2 mg (24 h) severe

Respiratory sensitization: No data available.

Skin sensitization: No data available.

Individuals have reported sensitivity to some of the components.

Germ Cell Mutagenicity: Mutagenic Category 1B

Benzene: cytogenic analysis, human inhalation: 0.1 ppm

2,2,4-Trimethylpentane, rat: 500 mg/kg

Carcinogenicity: Category 1B

Listed as a Carcinogen/Potential Carcinogen X Yes No

IARC: Benzene is listed by IARC as Group 1, carcinogenic to humans; gasoline is listed by IARC as Group 2b, possibly carcinogenic to humans; toluene is listed by IARC as Group 3, not classifiable.

NTP: Benzene is listed by NTP as known human carcinogen;

OSHA: Benzene is on the list of OSHA identified carcinogens.

Reproductive Toxicity: Category 2

Toluene, Rat, Inhalation, TClO: 1500 ppm (7 to 20 days pregnant)

Benzene, Rat Inhalation, TClO: 50 ppm (24 h, 7 to 14 days pregnant)

STOT, Single Exposure: Category 3, Central Nervous System Depressant

Gasoline and the individual components have shown central nervous system depressant effects.

STOT, Repeated Exposure: Category 1

Benzene may affect blood and kidney systems.

Aspiration Hazard: Category 1

Gasoline, toluene, *n*-hexane, *n*-pentane, 2,2,4-trimethylpentane, and benzene are aspiration hazards.

12. ECOLOGICAL INFORMATION

Ecotoxicity Data: *Components of Reformulated Gasoline in SRM 2298 with ecotoxicity data are listed.*

| Components | Aquatic Toxicity |
|--------------|---|
| Gasoline | Fish: 96 Hr LC50 Rainbow trout (<i>Oncorhynchus mykiss</i>): 56 mg/L Algae: 72 Hr EC50 <i>Pseudokirchneriella subcapitata</i> : 4700 mg/L |
| Toluene | Fish: 96 Hr LC50 Rainbow trout (<i>Oncorhynchus mykiss</i>): 5.8 mg/L [semi-static] Algae: 96 Hr EC50 <i>Pseudokirchneriella subcapitata</i> : >433 mg/L Invertebrate: 48 Hr EC50 Freshwater water flea (<i>Daphnia magna</i>): 5.46-9.83 mg/L |
| n-Hexane | Fish: 96 Hr LC50 Fathead minnow (<i>Pimephales promelas</i>): 2.1-2.98 mg/L [flow-through] Invertebrate: 24 Hr EC50 Freshwater water flea (<i>Daphnia magna</i>): >1000 mg/L |
| Benzene | Fish: 96 Hr LC50 Rainbow trout (<i>Oncorhynchus mykiss</i>): 5.3 mg/L [flow-through] Algae: 72 Hr EC50 <i>Pseudokirchneriella subcapitata</i> : 29 mg/L Invertebrate: 48 Hr EC50 Freshwater water flea (<i>Daphnia magna</i>): 9–16 mg/L [static] |
| Cyclopentane | Invertebrate: Freshwater water flea (<i>Daphnia magna</i>) EC50: 10.5 mg/L (48 h) |
| Isopentane | Invertebrate: Freshwater water flea (<i>Daphnia magna</i>) EC50: 2.3 mg/L (48 h) |
| n-Pentane | Fish: Rainbow trout (<i>Oncorhynchus mykiss</i>) LC50: 5.8 mg/L (96 h) [semi-static] Invertebrate: Freshwater water flea (<i>Daphnia magna</i>) EC50: 9.74 mg/L (48 h) |

Persistence and Degradability: No data available.

Bioaccumulative Potential: Bioconcentration factors: benzene (3.5 to 4.4, species fish).

Mobility in Soil: No data available.

Other Adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose in accordance with all applicable federal, state, and local regulations. Subject to hazardous waste regulations US EPA 40 CFR 262:

| | |
|-----------|--|
| Gasoline: | Hazardous waste number D018 for concentrations at or above the regulatory level (0.05 mg/L); Hazardous waste number D001. |
| Toluene | Hazardous waste number U220. |
| Benzene | Hazardous waste number U019, ignitable waste, toxic waste, regulatory level 0.5 mg/L. |

14. TRANSPORTATION INFORMATION

U.S. DOT and IATA: UN1203; Gasoline; Hazard Class 3; Packing Group II.

15. REGULATORY INFORMATION

U.S. Regulations

CERCLA Sections 102a/103 (40 CFR 302.4): Final RQ listed below.

| | |
|-----------|--------------------|
| Toluene: | 1000 lbs (454 kg) |
| n-Hexane: | 5000 lbs (2270 kg) |
| Benzene: | 10 lbs (4.54 kg) |

SARA Title III Section 302 (40 CFR 355.30): None of the components are regulated.

SARA Title III Section 304 (40 CFR 355.40): None of the components are regulated.

SARA Title III Section 313 (40 CFR 372.65):

| | |
|-----------|--------------------------------|
| Toluene: | 1.0 % de minimis concentration |
| n-Hexane: | 1.0 % de minimis concentration |
| Benzene: | 0.1 % de minimis concentration |

OSHA Process Safety (29 CFR 1910.119): None of the components are regulated.

SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21):

| | |
|-----------------|-----|
| ACUTE HEALTH: | Yes |
| CHRONIC HEALTH: | Yes |
| FIRE: | Yes |
| REACTIVE: | No |
| PRESSURE: | No |

State Regulations

California Proposition 65:

WARNING! This product contains chemicals (benzene, toluene) known to the state of California to cause reproductive developmental effects.

WARNING! This product contains chemicals (benzene) known to the state of California to cause cancer.

U.S. TSCA Inventory: Gasoline, toluene, xylenes, *n*-hexane, and benzene are listed.

TSCA 12(b), Export Notification: Not listed.

Canadian Regulations: WHMIS Information is not provided for this material.

16. OTHER INFORMATION

Issue Date: 10 February 2017

Sources: ChemADVISOR, Inc., SDS *1,2,4-Trimethylbenzene*, 09 December 2015.
ChemADVISOR, Inc., SDS *1,3,5-Trimethylbenzene*, 19 June 2014.
ChemADVISOR, Inc., SDS *Benzene*, 09 December 2015.
ChemADVISOR, Inc., SDS *Ethyl Benzene*, 09 December 2015.
ChemADVISOR, Inc., SDS *Gasoline, Automotive, Unleaded*, 19 June 2014.
ChemADVISOR, Inc., SDS *n-Hexane*, 09 December 2015.
ChemADVISOR, Inc., SDS *m-Xylene*, 09 December 2015.
ChemADVISOR, Inc., SDS *p-Xylene*, 09 December 2015.
ChemADVISOR, Inc., SDS *o-Xylene*, 09 December 2015.
ChemADVISOR, Inc., SDS *Naphthalene*, 09 December 2015.
ChemADVISOR, Inc., SDS *Xylene*, 09 December 2015.
ChemADVISOR, Inc., SDS *Toluene*, 09 December 2015.
ExxonMobil, MSDS, *Gasoline, Unleaded Automotive*, 20 November 2009.
ExxonMobil, MSDS, *Gasoline, Unleaded Automotive*, 12 April 2016.

Key of Acronyms:

| | | | |
|--------|---|-------|--|
| ACGIH | American Conference of Governmental Industrial Hygienists | NTP | National Toxicology Program |
| CAS | Chemical Abstracts Service | OSHA | Occupational Safety and Health Administration |
| CERCLA | Comprehensive Environmental Response, Compensation, and Liability Act | PEL | Permissible Exposure Limit |
| CFR | Code of Federal Regulations | RCRA | Resource Conservation and Recovery Act |
| DOT | Department of Transportation | REL | Recommended Exposure Limit |
| EINECS | European Inventory of Existing Commercial Chemical Substances | RQ | Reportable Quantity |
| EPCRA | Emergency Planning and Community Right-to-Know Act | RTECS | Registry of Toxic Effects of Chemical Substances |
| IARC | International Agency for Research on Cancer | SARA | Superfund Amendments and Reauthorization Act |
| IATA | International Air Transport Association | SCBA | Self-Contained Breathing Apparatus |
| IDLH | Immediately Dangerous to Life and Health | SRM | Standard Reference Material |
| LC50 | Lethal Concentration | STEL | Short Term Exposure Limit |
| LD50 | Median Lethal Dose or Lethal Dose, 50 % | STOT | Specific Target Organ Toxicity |
| LEL | Lower Explosive Limit | TLV | Threshold Limit Value |
| MSDS | Material Safety Data Sheet | TPQ | Threshold Planning Quantity |
| NFPA | National Fire Protection Association | TSCA | Toxic Substances Control Act |
| NIOSH | National Institute for Occupational Safety and Health | TWA | Time Weighted Average |
| NIST | National Institute of Standards and Technology | UEL | Upper Explosive Limit |
| n.o.s. | Not Otherwise Specified | WHMIS | Workplace Hazardous Materials Information System |

Disclaimer: Physical and chemical data contained in this SDS are provided only for use in assessing the hazardous nature of the material. The SDS was prepared carefully, using current references; however, NIST does not certify the data in the SDS. The values for this material are given in the NIST Certificate of Analysis.

Users of this SRM should ensure that the SDS in their possession is current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at <http://www.nist.gov/srm>.