

UNITED STATES DEPARTMENT OF COMMERCE  
NATIONAL BUREAU OF STANDARDS  
WASHINGTON 25, D. C.

**National Bureau of Standards**  
**Certificate**

Standard Sample Number 593

HYDROCARBON BLEND NUMBER 2

This standard is one of eight mixtures of pure hydrocarbons representative of those occurring in hydrocarbon fuels and blending stocks. These blends are primarily for use in the calibration of mass spectrometers. However, they may be useful in other spectro-metric instruments or gas chromatographic techniques.

The hydrocarbons used to prepare this sample are several C<sub>7</sub> paraffins found in typical catalytically cracked naphthas. The composition of this blend is given in the following table:

Compound	S. S. Number <sup>1</sup>	Amount of impurity, <sup>2</sup> mole %	Volume <sup>3</sup> %
n-Heptane	216a	0.01 ± 0.01	17 ± 0.1
2-Methylhexane	223	.23 ± .07	25 ± .1
3-Methylhexane <sup>4</sup>	224	.25 ± .15	30 ± .1
2,3-Dimethylpentane <sup>4</sup>	227	.25 ± .15	20 ± .1
2,4-Dimethylpentane	228	.17 ± .05	8 ± .01

Notes: <sup>1</sup> S. S. Number refers to NBS Standard Samples of Hydrocarbons

<sup>2</sup> Amounts of impurity were evaluated from measurement of freezing points by the procedure described in J. Res. NBS 35, 355 (1945) RP 1676. The indicated uncertainties are estimated limits of error,

<sup>3</sup> The indicated uncertainties are estimated from the limits of error of the transfer apparatus used.

<sup>4</sup> Impurity estimated by analogy with isomers subjected to similar purification.

A. V. Astin, Director

Washington 25, D. C., April 1, 1961

USCOMM-NBS-DC