

SAFETY DATA SHEET

1. SUBSTANCE AND SOURCE IDENTIFICATION

Product Identifier

SRM Number: 2261

SRM Name: Chlorinated Pesticides in Hexane (Nominal Mass Concentration 2 µg/mL)

Other Means of Identification: Not applicable.

Recommended Use of This Material and Restrictions of Use

This Standard Reference Material (SRM) is a solution of chlorinated pesticides in hexane and is intended primarily for use in the calibration of gas chromatographic instrumentation used for the determination of chlorinated pesticides. A unit of SRM 2261 consists of five 2 mL ampoules, each containing approximately 1.2 mL of a solution.

Company Information

National Institute of Standards and Technology
Standard Reference Materials Program
100 Bureau Drive, Stop 2300
Gaithersburg, Maryland 20899-2300

Telephone: 301-975-2200

FAX: 301-948-3730

E-mail: SRMMSDS@nist.gov

Website: <https://www.nist.gov/srm>

Emergency Telephone ChemTrec:
1-800-424-9300 (North America)
+1-703-527-3887 (International)

2. HAZARDS IDENTIFICATION

Classification

Physical Hazard: Flammable liquid, Category 2

Health Hazard: Skin Corrosion/Irritation, Category 2

Serious Eye Damage/Eye Irritation, Category 2B

Reproductive Toxicity, Category 2

Specific Target Organ Toxicity, – Single Exposure, Category 3

Specific Target Organ Toxicity – Repeat Exposure, Category 2

Aspiration Hazard, Category 1

Label Elements

Symbol



Signal Word

DANGER

Hazard Statement(s)

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315+H320 Causes skin and eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness

H373 May cause damage to organs (eyes, skin, respiratory system, central nervous system, liver, kidneys) through prolonged or repeated exposure (inhalation, ingestion, skin contact).

Precautionary Statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measure against static discharge.
P260	Do not breathe mist, vapors, or spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink, or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, eye protection, and face protection.
P301+P310	If swallowed: Immediately call a doctor.
P331	Do NOT induce vomiting.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P337+P313	If skin or eye irritation occurs: Get medical attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use regular dry chemical, carbon dioxide, water, or regular foam media for extinction.
P403+P233	Store in a well-ventilated place. Keep cool. Keep container tightly closed.
P405	Store locked up
P501	Dispose of contents and container according to local regulations.

Hazards Not Otherwise Classified: None.

Ingredients(s) with Unknown Acute Toxicity: None.

3. COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS

Substance: Hexane

Other Designations: Hexane (hexyl hydride; normal hexane; n hexane)

Note: This material contains trace amounts of compounds which have been reported to have toxic, mutagenic, and/or carcinogenic properties, and should be handled with care. These compounds are not listed as they are below the reportable limit for hazardous components (1 % or greater) and carcinogens (0.1 % or greater), required by OSHA, 29 CFR 1910.1200 (g)(2)(i)(C)(1), for SDS information. For actual concentrations, see the Certificate of Analysis.

Component(s)	CAS Number	EC Number (EINECS)	Nominal Mass Concentration (%)
n-Hexane	110-54-3	203-777-6	>99.9

4. FIRST AID MEASURES

Description of First Aid Measures

Inhalation: If adverse effects occur, remove to well-ventilated (uncontaminated) area. If breathing is difficult, qualified personnel may administer oxygen. If not breathing, qualified personnel should give artificial respiration. Seek immediate medical attention.

Skin Contact: Rinse affected skin with water for at least 15 minutes, then wash thoroughly with soap or mild detergent and water. If skin irritation persists, seek medical aid and bring the container or label.

Eye Contact: Immediately flush eyes, including under the eyelids, with copious amounts of water for at least 15 minutes. Seek immediate medical attention.

Ingestion: Contact local poison control immediately; if vomiting occurs, keep head lower than hips to prevent aspiration. If unconscious, turn head to side; get medical attention immediately.

Most Important Symptoms/Effects, Acute and Delayed: Respiratory tract irritation, skin irritation, eye irritation, aspiration hazard, central nervous system depression, and nerve damage.

Indication of any immediate medical attention and special treatment needed, if necessary: If any of the above symptoms are present, seek immediate medical attention.

5. FIRE FIGHTING MEASURES

Fire and Explosion Hazards: Severe fire hazard. Vapor/air mixtures are explosive above the flash point. Vapors or gases may ignite at distant ignition sources and flash back. See Section 9, "Physical and Chemical Properties" for flammability properties.

Extinguishing Media

Suitable: Regular dry chemical, carbon dioxide, water, or alcohol-resistant foam.

Unsuitable: None listed.

Specific Hazards Arising from the Chemical: Not applicable.

Special Protective Equipment and Precautions for Fire-Fighters: Move container from fire area if it can be done without personal risk. Avoid inhalation of material or combustion by-products. Wear full protective clothing and NIOSH-approved self-contained breathing apparatus (SCBA).

NFPA Ratings (0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Health = 2 Fire = 3 Reactivity = 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Use suitable protective equipment; see Section 8, "Exposure Controls and Personal Protection". Keep out of waters supplies and sewers.

Methods and Materials for Containment and Clean up: Avoid heat, flames, sparks, and other sources of ignition. Stop leak if possible without personal risk, with water spray to reduce vapors. Absorb spilled material with sand or non-combustible material and collect in appropriate container for disposal.

7. HANDLING AND STORAGE

Safe Handling Precautions: Open glass ampoules carefully to prevent contamination and injury. See Section 8, "Exposure Controls and Personal Protection".

Storage and Incompatible Materials: Store in a well-ventilated area. Keep separated from incompatible substances (oxidizing materials, halogens, combustible materials).

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits

NIOSH (REL): 180 mg/m³; 50 ppm (TWA)

3960 mg/m³; 1100 ppm (IDLH, 10 % LEL)

ACGIH (TLV): 180 mg/m³; 50 ppm (TWA)

Skin - potential significant contribution to overall exposure by the cutaneous route.

OSHA (PEL): 1800 mg/m³; 500 ppm (TWA)

Engineering Controls: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Personal Protection Measures: In accordance with OSHA 29 CFR 1910.132, subpart I, wear appropriate Personal Protective Equipment (PPE) to minimize exposure to this material.

Respiratory Protection: If workplace conditions warrant a respirator, a respiratory protection program that meets OSHA 29CFR 1910.134 must be followed. Refer to NIOSH 42 CFR 84 for applicable certified respirators.

Eye Protection: Splash resistant safety goggles and emergency eyewash are recommended.

Skin and Body Protection: Chemical resistant clothing and gloves are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Hexane >99.9%
Molar Mass (g/mol)	86.18
Molecular Formula	C ₆ H ₁₄
Appearance (physical state, color, etc.)	clear, colorless liquid
Odor	gasoline odor
Odor threshold	64 ppm to 244 ppm
pH	neutral
Evaporation rate (butyl acetate = 1)	15.8
Melting point/freezing point	-95 °C (-139 °F)
Relative Density as Specific Gravity (water = 1)	0.6603
Density	not available
Vapor Pressure	124 mmHg at 20 °C
Vapor Density (air = 1)	3.0
Viscosity	0.32 cP at 25 °C
Solubilities	water: 0.014 % at 20 °C solvents: alcohol, ether, chloroform, acetone, organic solvents.
Partition coefficient (n-octanol/water)	log Kow = 3.90
Thermal Stability Properties	
Autoignition Temperature	225 °C (437 °F)
Thermal Decomposition	not applicable
Initial boiling point and boiling range	69 °C (156 °F)
Explosive Limits, LEL (Volume %)	1.1 %
Explosive Limits, UEL (Volume %)	7.5 %
Flash Point (Closed Cup)	-22 °C (-7.6 °F)
Flammability (solid, gas)	not applicable

10. STABILITY AND REACTIVITY

Reactivity: This material is not reactive at normal temperatures and pressure.

Stability: Stable Unstable

Possible Hazardous Reactions: Not applicable.

Conditions to Avoid: Avoid heat, flames, sparks, and other sources of ignition. Minimize contact with material. Avoid inhalation of material or combustion by-products. Keep out of water supplies and sewers.

Incompatible Materials: Oxidizing materials, halogens, combustible materials.

Hazardous Decomposition: Oxides of carbon.

Hazardous Polymerization: Will Occur Will Not Occur

11. TOXICOLOGICAL INFORMATION

Route of Exposure: Inhalation Skin Ingestion

Symptoms Related to the Physical, Chemical and Toxicological Characteristics: Respiratory tract, skin, and eye irritation; aspiration hazard, nervous system depression, and nerve damage.

Potential Health Effects (Acute, Chronic, and Delayed)

Inhalation: Inhalation of hexane can cause eye, nose, throat and respiratory irritation. Acute exposure to considerable concentrations may cause cough, wheezing, headache, dizziness, nausea, gastrointestinal symptoms, central nervous system depression and asphyxia. Prolonged exposure may result in motor sensory and central nervous system abnormalities.

Skin Contact: Contact with liquid may cause irritation and dermatitis due to defatting.

15. REGULATORY INFORMATION

U.S. Regulations

CERCLA Sections 102a/103 (40 CFR 302.4): 5000 lbs (2270 kg) final RQ.
SARA Title III Section 302 (40 CFR 355.30): Not regulated.
SARA Title III Section 304 (40 CFR 355.40): Not regulated.
SARA Title III Section 313 (40 CFR 372.65): 1.0 % de minimis concentration.
OSHA Process Safety (29 CFR 1910.119): Not regulated.
SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21):
ACUTE HEALTH: Yes
CHRONIC HEALTH: Yes
FIRE: Yes
REACTIVE: No
PRESSURE: No

State Regulations: Not listed.

U.S. TSCA Inventory: Hexane is listed.

TSCA 12(b), Export Notification: Not listed.

Canadian Regulations: WHMIS Information is not provided for this material.

16. OTHER INFORMATION

Issue Date: 27 June 2018

Sources: ChemADVISOR, Inc., SDS *N-Hexane*, 09 December 2015.

Hazardous Substances Data Bank, National Library of Medicine, *Hexane CAS 110-54-3*, Full Record, available at <https://toxnet.nlm.nih.gov/cgi-bin/sis/htmlgen?HSDB> (accessed Jun 2018).

NIOSH Pocket Guide to Chemical Hazards, *Hexane CAS 110-54-3*, (4 April 2011), available at <https://www.cdc.gov/niosh/npg/npgd0322.html> (accessed Jun 2018); also see *RTECS #: MN9275000*, (May 2009); at <https://www.cdc.gov/niosh-rtecs/MN8D8678.html> (accessed Jun 2018).

Key of Acronyms:

ACGIH	American Conference of Governmental Industrial Hygienists	NTP	National Toxicology Program
CAS	Chemical Abstracts Service	OSHA	Occupational Safety and Health Administration
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act	PEL	Permissible Exposure Limit
CFR	Code of Federal Regulations	RCRA	Resource Conservation and Recovery Act
DOT	Department of Transportation	REL	Recommended Exposure Limit
EINECS	European Inventory of Existing Commercial Chemical Substances	RQ	Reportable Quantity
EPCRA	Emergency Planning and Community Right-to-Know Act	RTECS	Registry of Toxic Effects of Chemical Substances
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act
IATA	International Air Transport Association	SCBA	Self-Contained Breathing Apparatus
IDLH	Immediately Dangerous to Life and Health	SRM	Standard Reference Material
LC50	Lethal Concentration	STEL	Short Term Exposure Limit
LD50	Median Lethal Dose or Lethal Dose, 50 %	TLV	Threshold Limit Value
LEL	Lower Explosive Limit	TPQ	Threshold Planning Quantity
MSDS	Material Safety Data Sheet	TSCA	Toxic Substances Control Act
NFPA	National Fire Protection Association	TWA	Time Weighted Average
NIOSH	National Institute for Occupational Safety and Health	UEL	Upper Explosive Limit
NIST	National Institute of Standards and Technology	WHMIS	Workplace Hazardous Materials Information System
n.o.s.	Not Otherwise Specified		

Disclaimer: Physical and chemical data contained in this SDS are provided only for use in assessing the hazardous nature of the material. The SDS was prepared carefully, using current references; however, NIST does not certify the data in the SDS. The values for this material are given in the NIST Certificate of Analysis.

Users of this SRM should ensure that the SDS in their possession is current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at <https://www.nist.gov/srm>.