

SAFETY DATA SHEET

1. SUBSTANCE AND SOURCE IDENTIFICATION

Product Identifier

SRM Number: 25d

SRM Name: Manganese Ore

Other Means of Identification: Not applicable.

Recommended Use of This Material and Restrictions of Use

This Standard Reference Material (SRM) is intended primarily for use in validation of chemical and instrumental methods of analysis. A unit of SRM 25d consists of a bottle containing approximately 60 g of powder of particle size less than 74 µm (No. 200 sieve).

Company Information

National Institute of Standards and Technology

Standard Reference Materials Program

100 Bureau Drive, Stop 2300

Gaithersburg, Maryland 20899-2300

 Telephone: 301-975-2200
 Emergency Telephone ChemTrec:

 FAX: 301-948-3730
 1-800-424-9300 (North America)

 E-mail: SRMMSDS@nist.gov
 +1-703-527-3887 (International)

Website: http://www.nist.gov/srm

2. HAZARDS IDENTIFICATION

Classification

Physical Hazard: Not classified.

Health Hazard: Carcinogenic Category 1

STOT, Repeat Exposure Category 1

Label Elements

Symbol



Signal Word

DANGER

Hazard Statement(s)

H350 May cause lung cancer.

H372 Causes damage to lungs through prolonged or repeat inhalation.

Precautionary Statement(s)

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P280 Wear eye protection, protective gloves and clothing.
P308 + P313 If exposed or concerned: Get medical attention.

P405 Store locked up.

P501 Dispose of contents and container in accordance with local regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients(s) with Unknown Acute Toxicity: Not applicable.

SRM 25d Page 1 of 6

3. COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS

Substance: Manganese ore; mixture of the listed components.

Other Designations: Not applicable.

Components are listed in compliance with OSHA's 29 CFR 1910.1200. The material contains trace amounts of other oxide components; for the actual values see the NIST Certificate of Analysis.

Hazardous Component(s)	CAS Number	EC Number (EINECS)	Nominal Mass Concentration (%)
Manganese dioxide	1313-13-9	215-202-6	80
Iron	7439-89-6	231-096-4	<3
Silica, crystalline quartz	14808-60-7	238-878-4	<2

4. FIRST AID MEASURES

Description of First Aid Measures:

Inhalation: If adverse effects occur, remove to uncontaminated area. If not breathing, give artificial respiration or oxygen by qualified personnel. Seek immediate medical attention.

Skin Contact: Wash skin with soap and water.

Eye Contact: Flush eyes with water for at least 15 minutes. If necessary, seek medical attention.

Ingestion: If adverse effects occur after ingestion, seek medical treatment.

Most Important Symptoms/Effects, Acute and Delayed: Prolonged exposure to respirable silica particles can cause lung damage (silicosis) and cancer.

Indication of any immediate medical attention and special treatment needed, if necessary: If any of the above symptoms are present, seek medical attention if needed.

5. FIRE FIGHTING MEASURES

Fire and Explosion Hazards: Negligible fire hazard. Avoid generating dust. See Section 9, "Physical and Chemical Properties" for flammability properties.

Extinguishing Media:

Suitable: Use extinguishing agents appropriate for surrounding fire.

Unsuitable: None listed.

Specific Hazards Arising from the Chemical: None listed.

Special Protective Equipment and Precautions for Fire-Fighters: Avoid inhalation of material or combustion byproducts. Wear full protective clothing and NIOSH approved self-contained breathing apparatus (SCBA).

NFPA Ratings (0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Health = 1 Fire = 0 Reactivity = 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Any accumulated material on surfaces should be removed and properly disposed of. Use suitable protective equipment; see Section 8, "Exposure Controls and Personal Protection".

Methods and Materials for Containment and Clean up: Collect spilled material in appropriate container for disposal. Keep out of water supplies and sewers. Keep unnecessary people away, isolate hazard area and deny entry.

7. HANDLING AND STORAGE

Safe Handling Precautions: See Section 8, "Exposure Controls and Personal Protection". Avoid contact with incompatible materials (see Section 10, "Stability and Reactivity").

Storage: Store and handle in accordance with all current regulations and standards.

SRM 25d Page 2 of 6

8. Exposure Controls and Personal Protection

Exposure Limits					
Components	OSHA (PEL)	ACGIH (TLV)	NIOSH (REL)		
Manganese dioxide as Mn (as related to Manganese compounds)	Ceiling: 5 mg/m ³	TWA: 0.02 mg/m ³ TWA: 0.1 mg/m ³ (inorganic compounds)	TWA: 1 mg/m ³ STEL: 3 mg/m ³ IDLH: 500 mg/m ³		
Silica, crystalline quartz	TWA: 30/(SiO ₂ + 2) mg/m ³ (total dust) TWA: 10/(SiO ₂ +2) mg/m ³ (respirable fraction) TWA: 250/(SiO ₂ + 5) mppcf (respirable fraction)	TWA: 0.025 mg/m ³ (respirable fraction)	TWA: 0.05 mg/m ³ (respirable dust) IDLH: 50 mg/m ³ (respirable dust)		

Engineering Controls: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Personal Protection: In accordance with OSHA 29 CFR 1910.132, subpart I, wear appropriate Personal Protective Equipment (PPE) to minimize exposure to this material.

Respiratory Protection: If workplace conditions warrant a respirator, a respiratory protection program that meets OSHA 29CFR 1910.134 must be followed. Refer to NIOSH 42 CFR 84 for applicable certified respirators.

Eye/Face Protection: Wear splash resistant safety goggles with a face shield. An eye wash station should be readily available near areas of use.

Skin and Body Protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Chemical-resistant gloves should be worn at all times when handling chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES

Particle Size

Descriptive Properties Manganese Ore Appearance (physical state, color, etc.) solid gray powder Molecular Formula not applicable not applicable Molar Mass (g/mol) Odor not available **Odor threshold** not available not available **Evaporation rate** not available not available Melting point/freezing point not available **Density** not available Vapor Pressure (mmHg) Vapor Density (air = 1) not available Viscosity (cP) not available Solubility(ies) insoluble in water; soluble in hydrochloric acid not available Partition coefficient (n-octanol/water)

SRM 25d Page 3 of 6

<74 μm

Thermal Stability Properties Autoignition Temperature	Manganese dioxide not available
Thermal Decomposition	not available
Initial boiling point and boiling range	not available
Explosive Limits, LEL (Volume %)	not available
Explosive Limits, UEL (Volume %)	not available
Flash Point	not available
Flammability (solid, gas)	not available
10. STABILITY AND REACTIVITY	
Reactivity: Stable at normal temperatures and pressure.	
Stability: X Stable Unstab	le
Possible Hazardous Reactions: None listed.	
Conditions to Avoid: Avoid generating dust. Avoid h contact with incompatible materials.	eat, flames, sparks, and other sources of ignitions. Avoid
Incompatible Materials: Metals, oxidizing material combustible materials, metal carbide, and bases.	s, halogens, acids, peroxides, reducing agents, amines,
Fire/Explosion Information: See Section 5, "Fire Fight	ing Measures".
Hazardous Decomposition: Thermal decomposition will	l produce miscellaneous compounds.
Hazardous Polymerization: Will Occur	X Will Not Occur
11. TOXICOLOGICAL INFORMATION	
Route of Exposure: X Inhalation X	Skin Ingestion
Symptoms Related to the Physical, Chemical and Todisorders. May cause irritation, lung damage, silicosis, and	oxicological Characteristics: May aggravate respiratory and cancer.
	repeated exposure to mixtures containing respirable silica pharyngitis, chronic bronchitis, emphysema, and silicosis.
Skin Contact: May cause mechanical irritation.	
Eye Contact: May cause irritation or eye damage.	
Ingestion: May cause irritation.	
Numerical Measures of Toxicity Acute Toxicity: Not classified. Manganese dioxide: Rat, Oral LD50: >3478 mg Iron: Rat, Oral LD50: 30 g/kg	g/kg; 9000 mg/kg
Skin Corrosion/Irritation: No data available.	
Serious Eye Damage/Eye irritation: No data availa	able.
Respiratory Sensitization: No data available.	
Skin Sensitization: No data available.	
Germ Cell Mutagenicity: No data available.	
Carcinogenicity: Category 1.	
Listed as a Carcinogen/Potential Carcinogen Manganese dioxide and iron are not listed by IA Tumorigenic data: Rat, intratracheal, TDLo	X Yes No RC, NTP or OSHA as carcinogen/potential carcinogens. : 450 mg/kg (15 week)
Silica, crystalline quartz is listed as Group 1, ca (respirable size) by NTP, and is not listed by OS Tumorigenic data: Rat, Inhalation, TCLo: Mutagenic data: Human, 120 mg/L (24 h)	

SRM 25d Page 4 of 6

Reproductive Toxicity: No data available.

Specific Target Organ Toxicity, Single Exposure: No data available.

Specific Target Organ Toxicity, Repeated Exposure: Category 1, Lungs.

Repeated and prolonged exposure to manganese dust particles may cause systemic poisoning called "manganism". Repeated and prolonged exposure to respirable quartz may cause chronic bronchitis, emphysema, and silicosis.

Aspiration hazard: Not applicable.

12. ECOLOGICAL INFORMATION

Ecotoxicity Data: No data available.

Persistence and Degradability: No data available.

Bioaccumulative Potential: No bioaccumulation expected.

Mobility in Soil: No data available.

Other Adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of waste in accordance with all applicable federal, state, and local regulations.

14. TRANSPORTATION INFORMATION

U.S. DOT and IATA: Not regulated by DOT or IATA.

15. REGULATORY INFORMATION

U.S. Regulations:

CERCLA Sections 102a/103 (40 CFR 302.4): Not regulated.

SARA Title III Section 302 (40 CFR 355.30): Not regulated.

SARA Title III Section 304 (40 CFR 355.40): Not regulated.

SARA Title III Section 313 (40 CFR 372.65): 1 % de minimis concentration (related to Mn compounds)

OSHA Process Safety (29 CFR 1910.119): Not regulated.

SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21):

ACUTE HEALTH: No
CHRONIC HEALTH: Yes
FIRE: No
REACTIVE: No
PRESSURE: No

State Regulations:

California Proposition 65: Warning! This product contains a chemical (quartz) known to the state of California to cause cancer.

U.S. TSCA Inventory: Manganese dioxide, iron, and quartz are listed.

TSCA 12(b), Export Notification: Not listed.

Canadian Regulations: WHMIS Information is not provided for this material.

SRM 25d Page 5 of 6

16. OTHER INFORMATION

Issue Date: 30 January 2015

Sources: ChemADVISOR, Inc., SDS, Manganese Ore, Chemical Grade, 10 September 2014.

ChemADVISOR, Inc., SDS, Quartz, 10 September 2014.

Key of Acronyms:

ACGIH American Conference of Governmental Industrial NRC Nuclear Regulatory Commission Hygienists	
ALI Annual Limit on Intake NTP National Toxicology Program	
CAS Chemical Abstracts Service OSHA Occupational Safety and Health Administrati	on
CERCLA Comprehensive Environmental Response, PEL Permissible Exposure Limit	
Compensation, and Liability Act	
CFR Code of Federal Regulations RCRA Resource Conservation and Recovery Act	
DOT Department of Transportation REL Recommended Exposure Limit	
EC50 Effective Concentration, 50 % RM Reference Material	
EINECS European Inventory of Existing Commercial RQ Reportable Quantity	
Chemical Substances	
EPCRA Emergency Planning and Community Right-to-Know RTECS Registry of Toxic Effects of Chemical Substa	nces
Act	
IARC International Agency for Research on Cancer SARA Superfund Amendments and Reauthorization	Act
IATA International Air Transportation Agency SCBA Self-Contained Breathing Apparatus	
IDLH Immediately Dangerous to Life and Health SRM Standard Reference Material	
LC50 Lethal Concentration, 50 % STEL Short Term Exposure Limit	
LD50 Lethal Dose, 50 % TLV Threshold Limit Value	
LEL Lower Explosive Limit TPQ Threshold Planning Quantity	
MSDS Material Safety Data Sheet TSCA Toxic Substances Control Act	
NFPA National Fire Protection Association TWA Time Weighted Average	
NIOSH National Institute for Occupational Safety and Health UEL Upper Explosive Limit	_
NIST National Institute of Standards and Technology WHMIS Workplace Hazardous Materials Information	System

Disclaimer: Physical and chemical data contained in this SDS are provided only for use in assessing the hazardous nature of the material. The SDS was prepared carefully, using current references; however, NIST does not certify the data in the SDS. The certified values for this material are given in the NIST Certificate of Analysis.

Users of this SRM should ensure that the SDS in their possession is current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at http://www.nist.gov/srm.

SRM 25d Page 6 of 6