

SAFETY DATA SHEET

1. SUBSTANCE AND SOURCE IDENTIFICATION

Product Identifier

SRM Number: 3074
SRM Name: Phthalates in Methanol
Other Means of Identification: Not applicable.

Recommended Use of This Material and Restrictions of Use

This Standard Reference Material (SRM) is a solution of one adipate and six phthalates in methanol intended primarily for use in the calibration of chromatographic instrumentation used for the determination of the certified components in the mixture. Because of its miscibility with water, this SRM can also be used to fortify samples with known amounts of the six phthalates. A unit of SRM 3074 consists of five 2 mL ampoules, each containing 1.2 mL of solution.

Company Information

National Institute of Standards and Technology
 Standard Reference Materials Program
 100 Bureau Drive, Stop 2300
 Gaithersburg, Maryland 20899-2300

Telephone: 301-975-2200
 FAX: 301-948-3730
 E-mail: SRMMSDS@nist.gov
 Website: <http://www.nist.gov/srm>

Emergency Telephone ChemTrec:
 1-800-424-9300 (North America)
 +1-703-527-3887 (International)

2. HAZARDS IDENTIFICATION

Classification

Physical Hazard: Flammable Liquid, Category 2
Health Hazard: Acute Toxicity, Oral, Category 3
 Acute Toxicity, Inhalation, Category 3
 Acute Toxicity, Dermal, Category 3
 Specific Target Organ Toxicity, - Single Exposure, Category 1

Label Elements

Symbol



Signal Word

Danger

Hazard Statement(s)

H225 Highly flammable liquid and vapor.
 H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.
 H370 Causes damage to eyes, kidney, liver, heart, central nervous system.

Precautionary Statement(s)

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
 P233 Keep container tightly closed.
 P241 Use explosion-proof electrical/ventilating/lighting equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.

P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/eye protection/protective clothing.
Response	
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P308+P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P330	Rinse mouth.
P303+P361+P353	If on skin (or hair): take off immediately all contaminated clothing. Rinse skin with water/shower.
P370+P378	In case of fire: use regular dry chemical, carbon dioxide, water, or alcohol-resistant foam.
Storage	
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
Dispose	
P501	Dispose of contents/container in accordance with local/regional/national/international programs.

Hazards Not Otherwise Classified: None.

Ingredients(s) with Unknown Acute Toxicity: None.

3. COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS

Substance: Methanol

Other Designations: Methyl alcohol; wood alcohol; methyl hydroxide; wood spirit; wood naphtha.

Hazardous Component(s) ^(a)	CAS Number	EC Number (EINECS)	Nominal Mass Concentration (%)
Methanol	67-56-1	200-659-6	>99.9
Dimethylphthalate	131-11-3	205-011-6	<0.01
Diethylphthalate	84-66-2	201-550-6	<0.01
Di- <i>n</i> -butylphthalate	84-74-2	201-557-4	<0.01
Benzylbutylphthalate	85-68-7	201-622-7	<0.01
<i>Bis</i> (2-ethylhexyl)phthalate	117-81-7	204-211-0	<0.01
Di- <i>n</i> -octylphthalate	117-84-0	204-214-7	<0.01

^(a) Components are listed in compliance with OSHA's 29 CFR 1910.1200. Phthalate components are below the reporting limit for OSHA and listed here for informational purposes only. The actual values for this material are given in the NIST Certificate of Analysis.

4. FIRST AID MEASURES

Description of First Aid Measures

Inhalation: If adverse effects occur, remove to well-ventilated (uncontaminated) area. If breathing is difficult, qualified personnel may administer oxygen. If not breathing, qualified personnel should give artificial respiration. Seek immediate medical attention.

Skin Contact: Rinse affected skin with water for at least 15 minutes, then wash thoroughly with soap or mild detergent and water. If skin irritation persists, seek medical aid and bring the container or label.

Eye Contact: Immediately flush eyes, including under the eyelids, with copious amounts of water for at least 15 minutes. Seek immediate medical attention.

Ingestion: If ingested, seek medical attention.

Most Important Symptoms/Effects, Acute and Delayed

Inhalation: Irritation, dizziness, tingling sensation, pain in extremities, tremors, loss of coordination, difficulty breathing, irregular heartbeat, visual disturbances, blindness, bluish skin color, convulsions, unconsciousness, and coma.

Skin Contact: Irritation.

Eye Contact: Irritation.

Ingestion: Same as most important symptoms/effects listed under inhalation.

Indication of any immediate medical attention and special treatment needed, if necessary: If any of the above symptoms are present, seek immediate medical attention.

5. FIRE FIGHTING MEASURES

Fire and Explosion Hazards: Severe fire hazard. Vapor/air mixtures are explosive above the flash point. Vapors or gases may ignite at distant ignition sources and flash back. See Section 9, “Physical and Chemical Properties” for flammability properties.

Extinguishing Media

Suitable: Regular dry chemical, carbon dioxide, water, or alcohol-resistant foam.

Unsuitable: None listed.

Specific Hazards Arising from the Chemical: Not applicable.

Special Protective Equipment and Precautions for Fire-Fighters: Move container from fire area if it can be done without personal risk. Avoid inhalation of material or combustion by-products. Wear full protective clothing and NIOSH-approved self-contained breathing apparatus (SCBA).

NFPA Ratings (0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Health = 2 Fire = 3 Reactivity = 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Use suitable protective equipment; see Section 8, “Exposure Controls and Personal Protection”. Keep out of waters supplies and sewers.

Methods and Materials for Containment and Clean up: Avoid heat, flames, sparks and other sources of ignition. Stop leak if possible without personal risk, with water spray to reduce vapors. Absorb spilled material with sand or non-combustible material and collect in appropriate container for disposal.

7. HANDLING AND STORAGE

Safe Handling Precautions: See Section 8, “Exposure Controls and Personal Protection”.

Storage and Incompatible Materials: Store in a well-ventilated area. Keep separated from incompatible substances (halo carbons, combustible materials, metals, oxidizing materials, halogens, metal carbide, bases, acids, and amines).

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits

OSHA (PEL): 260 mg/m³; 200 ppm TWA

ACGIH (TLV): 200 ppm TWA

250 ppm STEL

Skin – potential significant contribution to overall exposure by the cutaneous route.

NIOSH (REL): 260 mg/m³; 200 ppm TWA

325 mg/m³; 250 ppm STEL

6000 ppm IDLH

Potential for dermal absorption.

Engineering Controls: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Personal Protection Measures: In accordance with OSHA 29 CFR 1910.132, subpart I, wear appropriate Personal Protective Equipment (PPE) to minimize exposure to this material.

Respiratory Protection: If workplace conditions warrant a respirator, a respiratory protection program that meets OSHA 29CFR 1910.134 must be followed. Refer to NIOSH 42 CFR 84 for applicable certified respirators.

Eye Protection: Splash resistant safety goggles and emergency eyewash are recommended.

Skin and Body Protection: Chemical resistant clothing and gloves are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Methanol >99.9 %
Molar Mass (g/mol)	32.04
Molecular Formula	CH ₃ OH
Appearance (physical state, color, etc.)	clear, colorless liquid
Odor	alcohol odor
Odor threshold	100 ppm
pH	not available
Evaporation rate (butyl acetate = 1)	4.6
Melting point/freezing point	-94 °C (-137 °F)
Relative Density as Specific Gravity (water = 1)	0.7914
Density	not available
Vapor Pressure	97.25 mmHg at 20 °C
Vapor Density (air = 1)	1.11
Viscosity	0.59 cP at 20 °C
Solubilities	soluble in water solvent: ether, benzene, acetone, chloroform, ethanol, ketones, organic solvents
Partition coefficient (n-octanol/water)	not available
Thermal Stability Properties	
Autoignition Temperature	385 °C (725 °F)
Thermal Decomposition	not available
Initial boiling point and boiling range	65 °C (149 °F)
Explosive Limits, LEL (Volume %)	6 %
Explosive Limits, UEL (Volume %)	36 %
Flash Point (Closed Cup)	11 °C (51.8 °F)
Flammability (solid, gas)	not applicable

10. STABILITY AND REACTIVITY

Reactivity: This material is not reactive at normal temperatures and pressure.

Stability: Stable Unstable

Possible Hazardous Reactions: Not applicable.

Conditions to Avoid: Avoid heat, flames, sparks, and other sources of ignition. Minimize contact with material. Avoid inhalation of material or combustion by-products. Keep out of water supplies and sewers.

Incompatible Materials: Halo carbons, combustible materials, metals, oxidizing materials, halogens, metal carbide, bases, acids, and amines.

Hazardous Decomposition: Oxides of carbon.

Hazardous Polymerization: Will Occur Will Not Occur

11. TOXICOLOGICAL INFORMATION

Route of Exposure: Inhalation Skin Ingestion

Symptoms Related to the Physical, Chemical and Toxicological Characteristics: Skin irritation, eye irritation, central nervous system depression, and nerve damage. May cause blindness.

Potential Health Effects (Acute, Chronic, and Delayed)

Inhalation: Acute and chronic exposure may cause irritation, cough, ringing in the ears, constipation, headache, drowsiness, dizziness, tingling sensation, pain in extremities, tremors, loss of coordination, blood disorders, and nerve damage. Chronic exposure may also cause sensitivity to light, changes in blood pressure, digestive issues, difficulty breathing, irregular heartbeat, visual disturbances, blindness, bluish skin color, lung congestion, heart damage, kidney damage, liver damage, reproductive effects, effects on the brain, convulsions, unconsciousness, and coma.

Skin Contact: Acute and chronic exposure may result in irritation, absorption may occur, headache, drowsiness, loss of coordination, blood disorders, and nerve damage.

Eye Contact: Acute and chronic exposure may cause irritation; acute may cause eye damage.

Ingestion: Acute and chronic exposure may cause the same effects as listed for inhalation.

Numerical Measures of Toxicity

Acute toxicity: Category 3 for oral, inhalation, and dermal.

Human, Oral, LDLo: 143 mg/kg

Rat, Oral, LD50: 5628 mg/kg

Rat, Inhalation, LC50: 83.2 mg/L (4 h); 145 000 ppm (1 h); 64 000 ppm (4 h)

Rabbit, Dermal, LD50: 15 800 mg/kg

Skin corrosion/irritation: Not classified.

Rabbit, skin: 20 mg (24 h) moderate

Serious eye damage/eye irritation: Not classified.

Rabbit, eyes: 100 mg (24 h) moderate; 40 mg moderate

Respiratory sensitization: No data available.

Skin sensitization: No data available.

Germ Cell Mutagenicity: No data available.

Carcinogenicity: Not classified.

Listed as a Carcinogen/Potential Carcinogen _____ **Yes** _____ **X** **No**

Methanol is not listed by IARC, NTP, or OSHA as a carcinogen.

Tumorigenic: Rat, Inhalation, TCLo: 1000 ppm (2 years)

Mutagenic: Mouse, Oral TD: 1 g/kg (cytogenetic analysis)

Rat, Oral TD: 10 µmol/kg (DNA damage)

Human, lymphocyte TC: 300 mmol/L (DNA inhibition)

Reproductive Toxicity: No data available.

Specific target organ toxicity, single exposure: Category 1, Damage to organs < eyes, kidney, liver, heart, central nervous system>.

Specific target organ toxicity, repeated exposure: Not classified.

Aspiration hazard: Not applicable.

12. ECOLOGICAL INFORMATION

Ecotoxicity Data

Fish, Bluegill, (*Lepomis macrochirus*), LC50: 13 500 mg/L to 17 600 mg/L (96 h) flow-through

Methanol, Fish, Fathead minnow (*Pimephales promelas*), LC50: 28 200 mg/L (96 h) flow-through

Methanol, Fish, Fathead minnow (*Pimephales promelas*), LC50: >100 mg/L (96 h) static

Persistence and Degradability: No data available.

Bioaccumulative Potential: <10 species: fish.

Mobility in Soil: No data available.

Other Adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose in accordance with all applicable federal, state, and local regulations.

14. TRANSPORTATION INFORMATION

U.S. DOT and IATA: UN1230, Methanol, Hazard Class 3, 6.1, Packing Group II.

15. REGULATORY INFORMATION

U.S. Regulations

CERCLA Sections 102a/103 (40 CFR 302.4): 5000 lb (2270 kg) final RQ.
SARA Title III Section 302 (40 CFR 355.30): Not regulated.
SARA Title III Section 304 (40 CFR 355.40): Not regulated.
SARA Title III Section 313 (40 CFR 372.65): 1.0 % de minimis concentrations.
OSHA Process Safety (29 CFR 1910.119): Not regulated.
SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21):

ACUTE HEALTH:	Yes
CHRONIC HEALTH:	Yes
FIRE:	Yes
REACTIVE:	No
PRESSURE:	No

State Regulations: California Proposition 65: WARNING! This product contains a chemical (methanol) known to the state of California to cause reproductive/developmental effects.

U.S. TSCA Inventory: Methanol is listed.

TSCA 12(b), Export Notification: Not listed.

Canadian Regulations: WHMIS Information: Not provided for this material.

16. OTHER INFORMATION

Issue Date: 21 August 2013

Sources: ChemADVISOR, Inc., MSDS *Methyl Alcohol*, 17 June 2013.

CDC, NIOSH, *Methanol*, RTECS# PC1400000, CAS No. 67-56-1; available at <http://www.cdc.gov/niosh-rtecs/PC155CC0.html> (accessed Aug 2013).

Key of Acronyms:

ACGIH	American Conference of Governmental Industrial Hygienists	NTP	National Toxicology Program
CAS	Chemical Abstracts Service	OSHA	Occupational Safety and Health Administration
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act	PEL	Permissible Exposure Level
CFR	Code of Federal Regulations	RCRA	Resource Conservation and Recovery Act
DOT	Department of Transportation	REL	Recommended Exposure Limit
EINECS	European Inventory of Existing Commercial Chemical Substances	RQ	Reportable Quantity
EPCRA	Emergency Planning and Community Right-to-Know Act	RTECS	Registry of Toxic Effects of Chemical Substances
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act
IATA	International Air Transportation Agency	SCBA	Self-Contained Breathing Apparatus
IDLH	Immediately Dangerous to Life and Health	SRM	Standard Reference Material
LC50	Lethal Concentration	STEL	Short Term Exposure Level
LD50	Median Lethal Dose or Lethal Dose, 50 %	TLV	Threshold Limit Value
LEL	Lower Explosive Limit	TPQ	Threshold Planning Quantity
MSDS	Material Safety Data Sheet	TSCA	Toxic Substances Control Act
NFPA	National Fire Protection Association	TWA	Time Weighted Average
NIOSH	National Institute for Occupational Safety and Health	UEL	Upper Explosive Limit
NIST	National Institute of Standards and Technology	WHMIS	Workplace Hazardous Materials Information System
n.o.s.	Not Otherwise Specified		

Disclaimer: Physical and chemical data contained in this SDS are provided only for use in assessing the hazardous nature of the material. The SDS was prepared carefully, using current references; however, NIST does not certify the data in the SDS. The values for this material are given in the NIST Certificate of Analysis.

Users of this SRM should ensure that the SDS in their possession is current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at <http://www.nist.gov/srm>.